


CLS LED Flat Panel Edge Lit



FEATURES:

- Standard dimming: 0-10V dimming
- Five year limited warranty
- CRI: ≥80
- Fits standard T-bar and narrow grid drop ceilings
- Available in 1'x4', 2'x2' and 2'x4' sizes
- Standard white finish
- IC Rated for direct insulation contact











PRODUCT DESCRIPTION:


Typically used to replace 2'x2' and 2'x4' fluorescent fixtures, the CLS Edge Lit LED Flat Panel Series is designed to lay in drop ceilings in offices, schools, and healthcare applications. The flat panels are fully dimmable, and are compatible with building controls, motion sensors, timers, and daylight harvesting systems.

The design of the panels produces an even, consistent shadowless light. The LEDs enable long life, high lumen maintenance, and are low maintenance and constructed without hazardous materials

Specifications

ltem Number	Rated Wattage*	LxWxH (ft)	CCT (Kelvin)*	Rate Flux (Lm) *	CRI (Ra)*	Pack Qty (Pcs)	Finishing Color	Dimmable
LED Panel Light								
CLS-PL2236SD-40K	36W	2x2x0.03	4000	4682	>80	4	White	Yes
CLS-PL2236SD-50K	36W	2x2x0.03	5000	4682	>80	4	White	Yes
CLS-PL2452SD-40K	50W	4x2x0.03	4000	6250	>80	2	White	Yes
CLS-PL2452SD-50K	50W	4x2x0.03	5000	6250	>80	2	White	Yes

Dimension Diagram



Item Number	L (ft)	W (ft)	H1 (ft)	H2 (ft)	Net Weight (Kg)
CLS-PL2236SD-40K	2	2	0.03	0.1	4.14±0.01
CLS-PL2236SD-50K	2	2	0.03	0.1	4.14±0.01
CLS-PL2452SD-40K	4	2	0.03	0.1	7.86±0.01
CLS-PL2452SD-50K	4	2	0.03	0.1	7.86±0.01