

NAME: LED Retrofit Kit

P/N: 1503610X

Note : The Letter X in P/N stands for Lamp base type, "1" for E39 lamp base, "2" for EX39 lamp base.

Advantage


- UL DLC certificate
- PHILIPS LUMILEDS chip, high CRI.
- 90*150 Degree, Type III.
- Internal driver, input voltage AC100-277V.
- E39 EX39 lamp base.
- Lamp base: 270 degree rotated.
- New style and high efficient wide-range input.
- Long lifespan and good heat dissipation.
- Direct replacement for Metal Halide, easy installation.
- Fits many different fixtures to replace traditional lamps.

Application

Replacement Lamps for Outdoor Pole/Arm-mounted Area and Roadway Luminaires (Type B).

PRODUCT SPECIFICATIONS		
Product Name	LED Retrofit Kit	
Part No	15036101	15036102
Lamp Base	E39	EX39
Dimension	243*113*80 MM	245*113*80 MM
TECHNICAL CHARACTERISTICS		
Color Temperature	4000K, 5000K, 5700K	
CRI	> 70	
Lumen in Luminaires	4000-4300 LM	
Lumen Efficacy in Luminaires	110-120 LM/W	
Input Power	36W	
Viewing Angle	90*150 Degree (Type III)	
Input Voltage	AC100-277V 50/60Hz	
PFC	>0.9	
Equivalent	80W CFL, 150W MHL/HPS/HID	
Waterproof Rating	IP51	
MATERIALS		
LED Brand	PHILIPS LUMILEDS	
LED Type	LUXEON 3030 2D (1.5W)	
LED QTY	84 PCS	
Housing	Magnesium Alloy+AL+PC	
Housing Color	Black+Silver	
OTHERS		
Operating Temperature	-20°C TO 45°C	
Operating Humidity	20% - 70% RH	
Storage Temperature	-30°C TO 80°C	
Storage Humidity	10% - 75% RH	
Application	Replacement Lamps for Outdoor Pole/Arm-mounted Area and Roadway Luminaires(Type B).	
Safety Certification	UL, DLC	
Warranty Time	5 Years	


Package



	Size	Qty/ Carton	Net Weight/ Carton	Gross Weight/ Carton
Inner box	290*135*105 MM	1 PC	0.72 KG	0.88 KG
Outer box	560*305*230 MM	8 PCS	5.8 KG	7.9 KG

Notice For User

- Please turn off power before install or change assembly parts.
- The input voltage and lamps should be matched, after connecting the power line, please make sure the wiring section is insulated.
- Make sure to remove or bypass the ballast in the fixtures before install the lamps.
- Suitable for damp locations. Do not use with dimmers.
- Suitable for use in enclosed luminaires, min. lamp compartment dimensions: 380*200*200MM.
- No-professionals, must not install and disassemble the lamps.



Trouble Shootings

Troubles	Check points
Flickering of the lamps	Turn off the power and turn on again in 3 minutes. If same phenomena occur, then call agencies
Out of working	Please check the connection